

PERFORMANCE DATA – GLP Series(Internal lobe/Gerotor) PUMPS



Type	Speed/ RPM	Port Size	CAPACITY(Q) Lt./Min						Weight in Kgs. (Approx)
			PRESSURE Kg./Cm ²						
			0		5		8		
			Q	HP	Q	HP	Q	HP	
GLP-06	1400	6NB/¼"	4.0	0.15	3.5	0.18	3.0	0.20	1.0
GLP-15	1400	15NB/½"	11.5	0.20	11.0	0.35	10.0	0.45	3.5
GLP-20	1400	20NB/¾"	17.0	0.30	16.3	0.50	15.0	0.75	4.0
GLP-25	1400	25NB/1"	45.0	0.45	43.0	0.75	40.0	1.0	6.0
GLP-40	1400	40NB/1½"	90.0	0.65	83.0	1.10	80.0	1.95	8.0

Specifications are subject to alteration, capacities are based on oils having viscosity of 35 cst.

Applications :-Common gerotor pump applications include, but are not limited to:
fuel oils ,Lube oil Cooking oils Hydraulic fluid etc.

Materials Of Construction / Configuration Options

Externals (head, casing) - Cast iron

Internals (rotor, idler) - Steel Alloy

Bushing - Carbon graphite, bronze, and other materials as needed

Shaft Seal - Lip seals, component mechanical seals

For- Crude Oil, Enamel, Edible Oils, Fatty Acid, Diesel, Fuel Oil (LDO, LSHS, HHS, RF, O), Kerosene, Lubricating Oil, Naphtha.

APEX PUMPS LIMITED

(AN ISO9001:2000 COMPANY)

G-228,RIICO INDUSTRIAL AREA, SITAPURA, JAIPUR-302022.

apex_pumps@rediffmail.com

Delhi Address- 14A/90, W.E.A., Karol Bagh, New Delhi- 110005.

Mobile-9810461516